

barbas.

EU-declaration of conformity

This EC declaration of conformity applies to the product described below and describes the conformity with the following directives:

2009/125/EC Directive for the setting of eco-design requirements for energy-related products (eco-design directive)

Relevant Regulation: (EU) 2015/1185

Declaration of Performance

No. 1.240.084-3 - CPR-2013/07/01

Unique identification code of the product type:	BOX 25 55 with support frame
Intended use:	Space heating in residential buildings
Manufacturer:	Barbas Bellfires BV; Hallenstraat 17; 5531 AB Bladel; The Netherlands
System of AVCP:	3
Harmonised technical specifications:	EN 16510-2-1:2022
Notified body:	No. 1639

Essential characteristics

Mechanical resistance and stability		Load bearing capacity		120 kg	
Safety in case of fire - Protection of combustible materials		Minimum distance to combustible materials			
Bottom (d _B):		3 cm			
Floor in front (d _F):		20-50			
Ceiling (d _C):		75 cm			
Rear (d _R):		non flammable wall			
Side (d _S):		20 cm			
Side radiation area (d _L):		40 cm			
Front (d _P):		120 cm			
Hygiene, health and the environment		<u>At nominal heat output</u>		<u>At part load heat output</u>	
Carbon monoxide emission (CO)		1131 mg/m3		1416 mg/m3	
Nitrogen oxides emission (NO _x)		98 mg/m3		129 mg/m3	
Emission of organic gaseous carbon (OGC)		74 mg/m3		187 mg/m3	
Particulate matter emission (PM)		32 mg/m3		80 mg/m3	
Safety and accessibility in use		Data for installation to a chimney			
		<u>At nominal heat output</u>		<u>At part load heat output</u>	
Flue gas outlet temperature		354 °C		331 °C	
Minimum flue draught		12 Pa		12 Pa	
Flue gas mass flow		9.0 g/s		9.3 g/s	
Fire safety of installation to the chimney		T400 G			
Energy economy and heat retention		Appliance's thermal heat output and energy efficiency			
		<u>At nominal heat output</u>		<u>At part load heat output</u>	
Space heat output		8.8 kW		4.9 kW	
Efficiency		76.0 %		64.8 %	
Seasonal space heating efficiency		66.0 %		Space heating efficiency	
Energy efficiency index (EEI)		100			
Energy efficiency class		A			
		<u>At nominal heat output</u>		<u>At part load heat output</u>	
Electric power consumption		NPD		NPD	
Sustainable use of natural resources					
Environmental sustainability		NPD			

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Danny Baijens, CEO



Bladel, The Netherlands
20 February 2026