

barbas.

EU-declaration of conformity

This EC declaration of conformity applies to the product described below and describes the conformity with the following directives:

2009/125/EC Directive for the setting of eco-design requirements for energy-related products (eco-design directive)

Relevant Regulation: (EU) 2015/1185

Declaration of Performance

No. 1.232-083-4 - CPR-2013/07/01

Unique identification code of the product type:	BOX 25 75 with wood log storage module
Intended use:	Space heating in residential buildings
Manufacturer:	Barbas Bellfires BV; Hallenstraat 17; 5531 AB Bladel; The Netherlands
System of AVCP:	3
Harmonised technical specifications:	EN 16510-2-1:2022
Notified body:	No. 2013


Essential characteristics

Mechanical resistance and stability			
Load bearing capacity	120 kg		
Safety in case of fire - Protection of combustible materials		Minimum distance to combustible materials	
Bottom (d _B):	0 cm		
Floor in front (d _F):	20 cm		
Ceiling (d _C):	75 cm		
Rear (d _R):	30 cm		
Side (d _S):	40 cm		
Side radiation area (d _L):	160 cm		
Front (d _P):	160 cm		
Rear with installed heat shield (d _R)	5 cm		
Hygiene, health and the environment	<u>At nominal heat output</u>	<u>At part load heat output</u>	
Carbon monoxide emission (CO)	1208 mg/m3	1617 mg/m3	
Nitrogen oxides emission (NO _x)	71 mg/m3	84 mg/m3	
Emission of organic gaseous carbon (OGC)	63 mg/m3	77 mg/m3	
Particulate matter emission (PM)	28 mg/m3	15 mg/m3	
Safety and accessibility in use	Data for installation to a chimney		
	<u>At nominal heat output</u>	<u>At part load heat output</u>	
Flue gas outlet temperature	349 °C	302 °C	
Minimum flue draught	12 Pa	7 Pa	
Flue gas mass flow	10.5 g/s	8.7 g/s	
Fire safety of installation to the chimney	T400 G		
Energy economy and heat retention	Appliance's thermal heat output and energy efficiency		
	<u>At nominal heat output</u>	<u>At part load heat output</u>	
Space heat output	10.9 kW	6.2 kW	
Efficiency	78.5 %	74 %	
	Space heating efficiency		
Seasonal space heating efficiency	68.5 %		
Energy efficiency index (EEI)	104		
Energy efficiency class	A		
	<u>At nominal heat output</u>	<u>At part load heat output</u>	<u>Standby mode</u>
Electric power consumption	NPD	NPD	NPD
Sustainable use of natural resources			
Environmental sustainability	NPD		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Danny Baijens, CEO



Bladel, The Netherlands
12 February 2026