

barbas.

EU-declaration of conformity

This EC declaration of conformity applies to the product described below and describes the conformity with the following directives:

2009/125/EC Directive for the setting of eco-design requirements for energy-related products (eco-design directive)

Relevant Regulation: (EU) 2015/1185

Declaration of Performance

No. 2.109.084-0 - CPR-2013/07/01

Unique identification code of the product type:	BOX 35-52-65 with support frame
Intended use:	Space heating in residential buildings
Manufacturer:	Barbas Bellfires BV; Hallenstraat 17; 5531 AB Bladel; The Netherlands
System of AVCP:	3
Harmonised technical specifications:	EN 16510-2-1:2022
Notified body:	No. 1639

Essential characteristics

Mechanical resistance and stability			
Load bearing capacity		120 kg	
Safety in case of fire - Protection of combustible materials		Minimum distance to combustible materials	
Bottom (d _B):		0 cm	
Floor in front (d _F):		20-50 cm	
Ceiling (d _C):		75 cm	
Rear (d _R):		non flammable wall	
Side (d _S):		30 cm	
Side radiation area (d _L):		50 cm	
Front (d _P):		120 cm	
Hygiene, health and the environment		<u>At nominal heat output</u>	<u>At part load heat output</u>
Carbon monoxide emission (CO)		608 mg/m ³	1447 mg/m ³
Nitrogen oxides emission (NO _x)		91 mg/m ³	78 mg/m ³
Emission of organic gaseous carbon (OGC)		36 mg/m ³	88 mg/m ³
Particulate matter emission (PM)		18 mg/m ³	13 mg/m ³
Safety and accessibility in use		Data for installation to a chimney	
		<u>At nominal heat output</u>	<u>At part load heat output</u>
Flue gas outlet temperature		368 °C	314 °C
Minimum flue draught		12 Pa	7 Pa
Flue gas mass flow		7.3 g/s	5.1 g/s
Fire safety of installation to the chimney		T400 G	
Energy economy and heat retention		Appliance's thermal heat output and energy efficiency	
		<u>At nominal heat output</u>	<u>At part load heat output</u>
Space heat output		8 kW	5 kW
Efficiency		77.6 %	78.4 %
Seasonal space heating efficiency		67.6 %	Space heating efficiency
Energy efficiency index (EEI)		103	
Energy efficiency class		A	
		<u>At nominal heat output</u>	<u>At part load heat output</u>
Electric power consumption		NPD	NPD
		<u>Standby mode</u>	
Environmental sustainability		NPD	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Danny Baijens, CEO



Bladel, The Netherlands

20 May 2026