

barbas.

EU-declaration of conformity

This EC declaration of conformity applies to the product described below and describes the conformity with the following directives:

2009/125/EC Directive for the setting of eco-design requirements for energy-related products (eco-design directive)

Relevant Regulation: (EU) 2015/1185

Declaration of Performance

No. 1.232-081-4 - CPR-2013/07/01

Unique identification code of the product type:	Evolux 65-40
Intended use:	Space heating in residential buildings
Manufacturer:	Barbas Bellfires BV; Hallenstraat 17; 5531 AB Bladel; The Netherlands
System of AVCP:	3
Harmonised technical specifications:	EN 16510-2-2:2022
Notified body:	No. 2013

Essential characteristics

Mechanical resistance and stability			
Load bearing capacity		N/A	
Safety in case of fire - Protection of combustible materials		Minimum distance to combustible materials	
Bottom (d _B):		0 cm	
Floor in front (d _F):		80 cm	
Ceiling (d _C):		0 cm	
Rear (d _R):		0 cm	
Side (d _S):		0 cm	
Side radiation area (d _L):		80 cm	
Front (d _P):		140 cm	
Insulation material:		10 cm plates with $\lambda \leq 0.1$ W/m.K	
Hygiene, health and the environment		At nominal heat output	At part load heat output
Carbon monoxide emission (CO)		1208 mg/m ³	1617 mg/m ³
Nitrogen oxides emission (NO _x)		71 mg/m ³	84 mg/m ³
Emission of organic gaseous carbon (OGC)		63 mg/m ³	77 mg/m ³
Particulate matter emission (PM)		28 mg/m ³	15 mg/m ³
Safety and accessibility in use		Data for installation to a chimney	
		At nominal heat output	At part load heat output
Flue gas outlet temperature		349 °C	302 °C
Minimum flue draught		12 Pa	7 Pa
Flue gas mass flow		10.5 g/s	8.7 g/s
Fire safety of installation to the chimney		T400 G	
Energy economy and heat retention		Appliance's thermal heat output and energy efficiency	
		At nominal heat output	At part load heat output
Space heat output		10.9 kW	6.2 kW
Efficiency		78.5 %	74 %
Seasonal space heating efficiency		67.8 %	Space heating efficiency
Energy efficiency index (EEI)		103	
Energy efficiency class		A	
		At nominal heat output	At part load heat output
Electric power consumption		0.064 kW	0.024 kW
			Standby mode
			0 kW
Sustainable use of natural resources			
Environmental sustainability		NPD	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Danny Baijens, CEO



Bladel, The Netherlands

24 April 2026