

Manufacturer					Barbas BV, Hallenstraat 17, 5531 AB Bladel, The Netherlands													
Product name					Barbas													
Model identifier					Gas Fire Smart Panorama 45-45 MF													
Equivalent models					N/A													
Test report nr.					200601986 by KIWA Nederland BV													
Harmonised European standards					EN 613:2021													
Indirect heating functionality					no													
Fuel type					gaseous													
Minimum permissible total flue duct length					1 meter vertical - 90° bend - 0,6 meter horizontal wall terminal													
Energy Efficiency Index (EEI) - [(EU)2015/1186]					88													
Fuel	Fuel type	Nitrogen oxides (NO _x) emission	Heat output						Efficiency (NCV)									
			Nominal heat output			Minimum heat output			Useful efficiency at nominal heat output			Useful efficiency at minimum heat output (indicative)			Seasonal space heating energy efficiency			
		[mg/kWh _{input}] (GCV)	Symbol	Value	Unit	Symbol	Value	Unit	Symbol	Value	Unit	Symbol	Value	Unit	Symbol	Value	Unit	
High calorific natural gas	G20	120	P _{nom}	4,5	kW	P _{min}	1,5	kW	η _{th,nom}	73,5	%	η _{th,min}	63,5	%	η _s	69,9	%	
Low calorific natural gas	G25	120	P _{nom}	4,2	kW	P _{min}	1,2	kW	η _{th,nom}	74,1	%	η _{th,min}	54,1	%	η _s	70,4	%	
Butane 30/37/50 mbar	G30	120	P _{nom}	3,9	kW	P _{min}	1,1	kW	η _{th,nom}	71,0	%	η _{th,min}	61,0	%	η _s	67,5	%	
Propane 30/37/50 mbar	G31	120	P _{nom}	3,3	kW	P _{min}	1,0	kW	η _{th,nom}	70,5	%	η _{th,min}	60,5	%	η _s	67,0	%	
Butane 28-30 mbar	G30	120	P _{nom}	3,9	kW	P _{min}	1,1	kW	η _{th,nom}	71,0	%	η _{th,min}	61,0	%	η _s	0,0	%	
Propane 37 mbar	G31	120	P _{nom}	3,3	kW	P _{min}	1,0	kW	η _{th,nom}	70,5	%	η _{th,min}	60,5	%	η _s	0,0	%	
Auxiliary power consumption																		
		Symbol	Value	Unit														
At nominal heat output		e _{lmax}	0,050	kW														
At minimum heat output		e _{lmin}	0,0003	kW														
Power consumption																		
		Symbol	Value	Unit														
In off-mode		P ₀	0	W														
In standby mode		P _{sm}	0,3	W														
In idle mode		P _{idle}	0	W														
In networked standby mode		P _{nsm}	0,3	W														
Standby mode with display of information or status		No																
Permanent pilot flame power requirement																		
		Symbol	Value	Unit														
Pilot flame power requirement (if applicable)		P _{pilot}	N/A	kW														
Type of heat output/room temperature control (select one)																		
single stage heat output, no room temperature control														no				
two or more manual stages, no room temperature control														no				
mechanic thermostat room temperature control														no				
electronic room temperature control														no				
electronic room temperature control plus day timer														no				
electronic room temperature control plus week timer														yes				
Other control options (multiple sections possible)																		
room temperature control, with presence detection														no				
room temperature control, with open window detection														no				
distance control option														yes				
adaptive start control														no				
working time limitation														no				
with black bulb sensor														no				
Self-learning functionality														yes				
control accuracy														yes				