

EU-declaration of conformity

This EC declaration of conformity applies to the product described below and describes the conformity with the following directives:

2009/125/EC Directive for the setting of eco-design requirements for energy-related products (eco-design directive)

Relevant Regulation: (EU) 2015/1185

Declaration of Performance

No. 1.825-5 - CPR-2013/07/01

Unique identification code of the product type:	Unilux-6 270 Three-sided
Intended use:	Space heating in residential buildings
Manufacturer:	Barbas Bellfires BV; Hallenstraat 17; 5531 AB Bladel; The Netherlands
System of AVCP:	3
Harmonised technical specifications:	EN 16510-2-2:2022
Notified body:	No. 2013

Essential characteristics

Mechanical resistance and stability			
Load bearing capacity		N/A	
Safety in case of fire - Protection of combustible materials		Minimum distance to combustible materials	
Bottom (d _B):		0 cm	
Floor in front (d _F):		50 cm	
Ceiling (d _C):		0 cm	
Rear (d _R):		0 cm	
Side (d _S):		50 cm	
Side radiation area (d _L):		50 cm	
Front (d _P):		120 cm	
Insulation material:		10 cm plates with $\lambda \leq 0.1$ W/m.K	
Hygiene, health and the environment		At nominal heat output	At part load heat output
Carbon monoxide emission (CO)		1071 mg/m ³	4337 mg/m ³
Nitrogen oxides emission (NO _x)		103 mg/m ³	101 mg/m ³
Emission of organic gaseous carbon (OGC)		74 mg/m ³	478 mg/m ³
Particulate matter emission (PM)		30 mg/m ³	91 mg/m ³
Safety and accessibility in use		Data for installation to a chimney	
		At nominal heat output	At part load heat output
Flue gas outlet temperature		346 °C	266 °C
Minimum flue draught		12 Pa	7 Pa
Flue gas mass flow		11.0 g/s	6.9 g/s
Fire safety of installation to the chimney		T400 G	
Energy economy and heat retention		Appliance's thermal heat output and energy efficiency	
		At nominal heat output	At part load heat output
Space heat output		9.7 kW	4.7 kW
Efficiency		78.8 %	74.1 %
Seasonal space heating efficiency		68.8 %	Space heating efficiency
Energy efficiency index (EEI)		104	
Energy efficiency class		A	
		At nominal heat output	At part load heat output
Electric power consumption		NPD	NPD
			Standby mode
			NPD
Sustainable use of natural resources			
Environmental sustainability		NPD	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Danny Baijens, CEO



Bladel, The Netherlands

02 July 2026