

barbas.

EU-declaration of conformity

This EC declaration of conformity applies to the product described below and describes the conformity with the following directives:

2009/125/EC Directive for the setting of eco-design requirements for energy-related products (eco-design directive)

Relevant Regulation: (EU) 2015/1185

Declaration of Performance

No. 1.813.003-7 - CPR-2013/07/01

Unique identification code of the product type:	Unilux-7 65
Intended use:	Space heating in residential buildings
Manufacturer:	Barbas Bellfires BV; Hallenstraat 17; 5531 AB Bladel; The Netherlands
System of AVCP:	3
Harmonised technical specifications:	EN 16510-2-2:2022
Notified body:	No. 2013

Essential characteristics

Mechanical resistance and stability				
	Load bearing capacity	N/A		
Safety in case of fire - Protection of combustible materials		Minimum distance to combustible materials		
	Bottom (d _B):	0 cm		
	Floor in front (d _F):	50 cm		
	Ceiling (d _C):	0 cm		
	Rear (d _R):	0 cm		
	Side (d _S):	0 cm		
	Side radiation area (d _L):	50 cm		
	Front (d _P):	120 cm		
	Insulation material:	10 cm plates with λ ≤ 0.1 W/m.K		
Hygiene, health and the environment		<u>At nominal heat output</u>	<u>At part load heat output</u>	
	Carbon monoxide emission (CO)	1061 mg/m3	2013 mg/m3	
	Nitrogen oxides emission (NO _x)	69 mg/m3	27 mg/m3	
	Emission of organic gaseous carbon (OGC)	86 mg/m3	168 mg/m3	
	Particulate matter emission (PM)	33 mg/m3	52 mg/m3	
Safety and accessibility in use		Data for installation to a chimney		
		<u>At nominal heat output</u>	<u>At part load heat output</u>	
	Flue gas outlet temperature	289 °C	242 °C	
	Minimum flue draught	12 Pa	6.5 Pa	
	Flue gas mass flow	7.6 g/s	5 g/s	
	Fire safety of installation to the chimney	T400 G		
Energy economy and heat retention		Appliance's thermal heat output and energy efficiency		
		<u>At nominal heat output</u>	<u>At part load heat output</u>	
	Space heat output	10 kW	5.5 kW	
	Efficiency	80.0 %	83.7 %	
	Seasonal space heating efficiency	70.0 %	Space heating efficiency	
	Energy efficiency index (EEI)	106		
	Energy efficiency class	A		
		<u>At nominal heat output</u>	<u>At part load heat output</u>	<u>Standby mode</u>
	Electric power consumption	NPD	NPD	NPD
Sustainable use of natural resources				
	Environmental sustainability	NPD		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Danny Baijens, CEO



Bladel, The Netherlands
10 March 2026